

STUMPJUMPER FSR EXPERT CARBON EVO 650b



HYP GRN/BLK

CARACTÉRISTIQUES TECHNIQUES

- Cadre FSR carbone FACT 9m, graphisme asymétrique racé, géométrie EVO avec des angles plus ouverts et le boîtier rabaisé pour plus de stabilité ; débattement 150mm, pivots à roulements annulaires étanches, boîtier de pédalier PF30, axe Ar. traversant de 142 x 12 pour plus de rigidité.
- Amortisseur FOX Float CTD Factory Boost Valve, avec AUTOSAG et revêtement Kashima. Trois positions: Montée / Trail / Descente et rebond ajustable
- Cintre Specialized aluminium Mini-Rise, 750mm et nouvelle fourche RockShox Pike RC, le meilleur compromis poids/rigidité, offrant de multiples options de réglage, 150mm de déb., et un axe traversant 15mm pour un pilotage précis.
- Pneus Specialized Butcher Control 2Bliss Ready et Purgatory Control en 2.3", Pour un meilleur contrôle et rendement sur terrain exigeant
- Roues Roval Traverse 142+ légères, mécanisme de roue libre DT Swiss, axe Av. traversant de 15mm, moyeu arrière 142+, compatible Tubeless Ready
- Transmission SRAM XX1 - 11 vitesses avec pédalier SRAM Carbon. Nouvelle tige de selle télescopique Specialized Command Post IR avec passage de gaine interne, commande au guidon pour changer instantanément la hauteur de selle et optimiser vos performances en montée et en descente

PART NO.	DESCRIPTION	COLOR	SIZE
93314-3402	EXPERT CARBON EVO 650B	HYP GRN/BLK	S
93314-3403			M
93314-3404			L
93314-3405			XL

SPECS

LES EQUIPEMENTS NE SONT PAS CONTRACTUELS ET PEUVENT VARIER SANS PRÉAVIS

FRAME	FACT 9m carbon front triangle, EVO geometry, FACT IS construction, M5 alloy rear triangle, tapered headtube, carbon PF30 BB, ISCG '05, internal Command Post IR routing, 142mm dropouts, sealed cartridge bearing pivots, replaceable derailleur hanger, 150mm travel
REAR SHOCK	Custom FOX Float CTD Factory w/ AUTOSAG and Boost Valve, Kashima coating, Climb, Trail, Descend settings and rebound adj., 195x51mm
FORK	RockShox Pike RC 650b, Solo Air spring, tapered alloy steerer, compression and rebound adj., 15mm thru-axle, 150mm travel
HEADSET	1-1/8 and 1-1/2" threadless, Campy style upper with 1-1/2" lower, cartridge bearings
STEM	Specialized XC, 3D forged alloy, 4-bolt, 6-degree rise, 31.8mm clamp
HANDLEBARS	Specialized All-Mountain, low-rise, 7050 alloy, 750mm wide, 8-degree backsweep, 6-degree upsweep, 31.8mm
GRIPS	Specialized Sip Grip, light lock-on, half-waffle, S/M: regular thickness, Others: XL
FRONT BRAKE	Shimano XT M-785, hydraulic disc, Ice Tech pads, S/M: 180mm rotor, Others: 200mm
REAR BRAKE	Shimano XT M-785, hydraulic disc, Ice Tech pads, S/M: 160mm rotor, Others: 180mm
BRAKE LEVERS	Shimano XT M-785, hydraulic disc
REAR DERAILLEUR	SRAM X01 X Horizon, 11-speed, carbon cage
SHIFT LEVERS	SRAM X01, 11-speed, trigger
CASSETTE	SRAM XG-1195, 11-speed, 10-42
CHAIN	SRAM X1, 11-speed w/ PowerLink
CRANKSET	Custom SRAM S-2200 carbon, PF30 spindle, S: 170mm, Others: 175mm
CHAINRINGS	34T
BOTTOM BRACKET	SRAM, PF30, OS press-in bearings, sealed cartridge
RIMS	Roval Traverse 650b, alloy disc, 28mm wide, 27/32h
FRONT HUB	Roval Traverse 650b, 15mm thru-axle end caps, 27h
REAR HUB	Roval Traverse 142+, XX1 driver body, 12mm thru-axle, 32h
SPOKES	DT Swiss Super Comp, stainless, 2.0/1.65/1.8mm
FRONT TIRE	Specialized Butcher Control, 60TPI, 2Bliss Ready, folding bead, 650bx2.3"
REAR TIRE	Specialized Purgatory Control, 60 TPI, 2Bliss Ready, folding bead, 650bx2.3"
INNER TUBES	Ultralight presta valve
SADDLE	Body Geometry Henge Comp, hollow Cr-Mo rails, 143mm
SEATPOST	Specialized Command Post IR, 3-position, internally routed adjustable height w/ air spring, remote operated, single bolt head, 30.9mm, S: 100mm travel, Others: 125mm
SEAT BINDER	Specialized 7050 alloy, single bolt, 34.9mm

STUMPJUMPER FSR COMP EVO 650b



MET BLK/HYP GRN/ MOTO GRN

CARACTÉRISTIQUES TECHNIQUES

- Cadre en aluminium M5 au graphisme asymétrique racé, géométrie EVO avec des angles plus ouverts et le boîtier rabaisé pour plus de stabilité ; débattement 150mm, pivots à roulements annulaires étanches, boîtier de pédalier PF30, axe Ar. traversant 142 x 12 pour plus de rigidité.
- Amortisseur FOX Float CTD Evolution avec AUTOSAG. Trois positions : Montée / Trail / Descente et rebond ajustable
- Fourche RockShox Revelation RC3, qui offre trois positions de réglage -ouvert, intermédiaire et fermé - avec rebond ajustable, 150mm de déb., et axe traversant 15mm
- Jantes Roval et moyeux Specialized Hi Lo, axe traversant 12mm qui accroît la rigidité, moyeu arrière 142+, compatible Tubeless Ready
- Transmission 2 x 10 vitesses avec pédalier SRAM S-1250 Custom
- Pneus Specialized Butcher Control 2Bliss Ready et Purgatory Control en 2.3", Pour un meilleur contrôle et rendement sur terrain exigeant.
- Freins à disque Shimano Deore pour un freinage performant
- Tige de selle télescopique Specialized Command Post BlackLite pour changer instantanément la hauteur de selle et optimiser vos performances en montée et en descente

PART NO.	DESCRIPTION	COLOR	SIZE
93315-2502	COMP EVO 650B	MET BLK/HYP GRN/ MOTO GRN	S
93315-2503			M
93315-2504			L
93315-2505			XL

SPECS

LES EQUIPEMENTS NE SONT PAS CONTRACTUELS ET PEUVENT VARIER SANS PRÉAVIS

FRAME	M5 hydroformed tubing, EVO geometry, tapered headtube, PF30 BB, ISCG '05, Command Post BlackLite routing, 142mm dropouts, sealed cartridge bearing pivots, replaceable derailleur hanger, 150mm travel
REAR SHOCK	Custom FOX Float CTD Evolution w/ AUTOSAG, Climb, Trail, Descend settings and rebound adj., 195x51mm
FORK	Custom RockShox Revelation RC3 650b, tapered alloy steerer, 3P damper w/ 3-position compression and rebound adj., 15mm thru-axle, 150mm travel
HEADSET	1-1/8 and 1-1/2" threadless, Campy style upper with 1-1/2" lower, cartridge bearings
STEM	Specialized XC, 3D forged alloy, 4-bolt, 6-degree rise, 31.8mm clamp
HANDLEBARS	Specialized All-Mountain, low-rise, 7050 alloy, 750mm wide, 8-degree backsweep, 6-degree upsweep, 31.8mm
GRIPS	Specialized Sip Grip, light lock-on, half-waffle, S/M: regular thickness, Others: XL
FRONT BRAKE	Shimano Deore M-615, hydraulic disc, Ice Tech pads, S/M: 180mm rotor, Others: 200mm
REAR BRAKE	Shimano Deore M-615, hydraulic disc, Ice Tech pads, S/M: 160mm rotor, Others: 180mm
BRAKE LEVERS	Shimano Deore M-615, hydraulic disc
FRONT DERAILLEUR	SRAM X7, 10-speed, S3 direct mount for DMD, bottom pull
REAR DERAILLEUR	SRAM X9 Type 2, 10-speed, mid cage
SHIFT LEVERS	SRAM X7, 10-speed, w/ MatchMaker clamp
CASSETTE	SRAM PG-1030, 10-speed, 11-36
CHAIN	PC 1051, 10-speed, w/ PowerLink, nickel finish
CRANKSET	Custom SRAM S-1250, 7050 alloy arms, 10-speed AM double, PF30 spindle, S: 170mm, Others: 175mm
CHAINRINGS	36/24, w/ alloy guard
BOTTOM BRACKET	SRAM, PF30, OS press-in bearings, sealed cartridge
RIMS	Roval 650b, alloy disc, 24mm wide, 32h
FRONT HUB	Specialized Hi Lo disc, sealed cartridge bearings, 15mm thru-axle, 32h
REAR HUB	Specialized Hi Lo disc, 4 sealed cartridge bearings, 12mm thru-axle, 32h
SPOKES	DT Swiss Industry, stainless
FRONT TIRE	Specialized Butcher Control, 60TPI, 2Bliss Ready, folding bead, 650bx2.3"
REAR TIRE	Specialized Purgatory Control, 60 TPI, 2Bliss Ready, folding bead, 650bx2.3"
INNER TUBES	Ultralight presta valve
SADDLE	Body Geometry Henge Comp, hollow Cr-Mo rails, 143mm
SEATPOST	Command Post BlackLite, alien head design, single bolt head, w/ remote adjust lever, 30.9mm, S: 100mm travel, Others: 125mm
SEAT BINDER	Specialized 7050 alloy, single bolt, 34.9mm